



+33 (0)4 78 68 98 40

NX PRODUCT COMPACT CHILLERS

SIZE 9-58

BODYWORK

Panel paint color RAL 9005

Frame on castor wheels

REFRIGERATION CIRCUIT

Scroll compressor, R32 fluid

Stainless steel plates evaporator

Thermostatic valve

Condenser with copper tubes and aluminum fins

Propeller-type axial fan

HYDRAULIC CIRCUIT

Stainless steel open buffer tank 60 liters (for NX9->24)

Stainless steel open buffer tank 100 liters (for NX36->58)

High-pressure stainless-steel pump 6 bar

Automatic discharge valve

Visual level, filling, draining

Industrial hoses

Hydraulic connections Inlet/Outlet 1''F

ELECTRICAL PANEL

Electronic controller with display (NFC/RS485)

Phase rotation controller

Motor thermal magnetic protection

Switch-disconnector

Network voltage AC 400V - 3ph - 50Hz



NX36-47-58



NX9-14-19-24

Package "e"

- Reinforce roof structure
- Generator positioning system
- Hydraulic connections in/out 3/4''M

TECHNICAL SPECIFICATIONS

NX PRODUCT	Cooling capacity	Water flow rate	Length	Width	Height	Weight
	kW	l/min	mm	mm	mm	kg
NX9	11.1	14	1048	682	1146	215
NX14	15.5	14	1048	682	1146	220
NX19	17.9	20	1048	682	1146	225
NX24	24.0	26	1048	682	1146	230
NX36	35.7	33	1498	682	1346	350
NX47	47.9	40	1498	682	1346	365
NX58	57.7	55	1498	682	1346	385

Outlet water temperature 20°C – Inlet air temperature 35°C